



เครื่องปรับอากาศ “แคเรียร์”



40LB Series

*Direct Expansion Fan Coil Unit
Duct Type*

36,000-98,000 BTU



พอก. 2134-2545

40LB Series



▲ 40LB Series (size: 004/006)



▲ 40LB Series (size: 007/009)

The New, Versatile & Energy Efficient 40LB Direct Expansion Fan Coil Unit.

The Carrier **40LB** Horizontal Type Direct Expansion Fan Coil Units come in 5 sizes covering an air flow range between (1,200 to 3,200) CFM. These units have been engineered for domestic and commercial application. When coupled with appropriate condensing units, the Carrier 40LB Fan Coil Units produce nominal capacities ranging from (36,000 to 98,000) Btu/hr.

Features

- Direct Driven Forward Curved Centrifugal Fan - quite operation.
- Carrier All Weather Cabinet - rugged and durable.
- Fire Retardant Insulation - minimises condensation & reduces sound levels.
- Aluminium Fin Corrugated - ensures high performance.
- Filter(s) - easily serviceable.
- Quick Lock Fittings - Easy & quick installation (40LB004 & 006 only).

Guide specifications

Furnish and install direct expansion fan coil units of the style and capacities as indicated on the plans and in the equipment schedules. Equipment schedules and specifications are based on Carrier 40LB Series direct expansion fan coil units.

The base units shall be complete with the direct expansion coils, centrifugal fans with PSC motors, condensate drain pan, filters and powder painted galvanized steel casing.

The coil shall be 3 row/13 FPI (40LB004 & 007) and 4 row/13 FPI (40LB006 & 009) and shall have 3/8" OD copper tubes with "Aluminium Fin Corrugated" pattern aluminium fins mechanically bonded. The coil shall be cleaned & leak tested at 1725 kPa minimum air pressure at the factory.

Drain pan shall be constructed from 18 SWG galvanized steel and coated with a layer of water proofing compound. The underside of this drain pan shall be insulated with a layer of fire retardant closed cell foam insulation. The drain connection shall be 3/4" OD sweat connection.

Motors shall be 3-speed permanent split capacitor type with built in thermal overload and mounted on resilient supports.

Fan shall be of the forward curved DIDW type, statically and dynamically balanced, and directly mounted on the motor shaft.

The filter shall comprise of an aluminium filter frame with 1/2" thick disposable filter media. (Optional)

Specifications

Description		Direct Expansion Fan Coil Unit				
Model		40LB				
		004G	004	006	007	009
Nominal Cooling Capacity	BTU/Hr	36,000*	48,000	60,000	78,000	98,000
Nominal Air Volume	CFM	1,200	1,600	2,000	2,400	3,200
Power Supply	V/Ph/Hz	220/1/50				
Fan	Type	Direct Driven DIDW Forward Curved Centrifugal Fan				
	Qty.	1		2		
Fan Motor	Type	Permanent Split Capacitor Type				
	Qty.	1		2		
	Power (HP)	3/4		2 x 3/4		
	Rated Load Amps	4.62		2 x 4.62		
	Speed	3-Speed				
Dimension	Height mm.	460				
	Width mm.	990		1,495		
	Depth mm.	648				
Connections	Liquid in.	3/8		1/2		
	Suction in.	3/4		1 1/8		
	Drain in.	3/4				
Net Weight	kg.	53	55	83	87	
Refrigerant		R-22				

Carrier reserves the right to make changes in specifications without prior notice. บริษัทฯ ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า

*เฉพาะรุ่น 36,000 BTU/H ผ่านการรับรองมาตรฐาน มอก. 2134-2545 (40LB004G/38LB036 or 38RE036)

Compatible with ▶



38LB Series



38RE Series



บริษัท แคนเรีย (ประเทศไทย) จำกัด
 ชั้น 14-15 อาคารเนชั่น ทาวเวอร์
 1858/63-74 ถ.บางนา-ตราด กม. 4.5
 บางนา กรุงเทพฯ 10260
 โทร. 0-2751-4777 แฟกซ์: 0-2751-4778

Carrier (Thailand) Ltd.
 14-15th Fl., Nation Tower,
 1858/63-74 Bangna-Trad Road Km. 4.5, Bangna,
 Bangkok 10260 Thailand
 Tel.: 0-2751-4777 Fax: 0-2751-4778

Daikin - Panasonic - Toshiba - Mitsubishi - Sanyo
 Sharp - Carrier - Trane - Reetech - LG - Samsung
 Hitachi - Sumikura - Nagakawa - Midea - Gree...

TU VẤN - THIẾT KẾ
 THI CÔNG - SỬA CHỮA
 Hợp đồng bảo trì dài hạn

CUNG CẤP THIẾT BỊ CHÍNH HÃNG
 Call: 0903152320 - Email: auietetc@gmail.com

Panasonic - Shneider - La - Mitsubishi
 Fuji - Shinjin - Delixi - Fuji - Chint
 CB - MCB - MCCB - ELCB - RCCB/RCCO - ACB
 Contactor - Relay nhiệt - Phích & ổ cắm công nghiệp
 Đèn báo - Nút nhấn - Contact - Đồng hồ A, V, ...