

## Non Inverter Mini Cassette Type



- 18,400 Btu/h 5.40kW
- 4-Way Airflow System
- LCD Wireless Remote Controller
- Random Auto Restart
- Removable Washable Panel

### CS-PC18DB4H (2 HP)

General Information	Indoor Model Number		CS-PC18DB4H
	Outdoor Model Number	Indoor [kW]	5.4
		Indoor [Btu/h]	18,400
	EER [Btu/hW]		(220V)10.5
	Cooling [msup3/sup/min]		12.8
Healthy Air Quality Features		Super Alleru-Buster Filter	Yes (option)
		Removable, Washable Panel	Yes
Comfortable Features	4-Way Air Deflection System	Width	575
		Height	260.0
		Depth	575.0
Product Dimensions	Panel [mm]	Width	700.0
		Height	51.0
		Depth	700.0
	Outdoor (per Unit) [mm]	Width	875.0
		Height	750.0
		Depth	345.0
Product Weight	Net Weight [kg]	Indoor	19.0
		Outdoor	56
Electricity	Rated Voltage		240V
	Power Frequency	Indoor (Cooling)	(220V)1.72kW (240V)1.85kW
Technical Features	Piping Connection	Liquid Side [mm]	6.35
		Liquid Side [inch]	1/4
		Gas Side [mm]	12.7
		Gas Side [inch]	1/2

	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)	25.0
Convenient Features	24-Hour ON OFF Real Setting Timer		Yes
	LCD Wireless Remote Controller		Yes
Reliable Features	Random Auto Restart		Yes
	Long Piping	Cooling	27C DB/19C WB 35C DB/24C WB

### CS-D24DB4H5 (2.5 HP)

## Non Inverter Cassette Type

- 25,000 Btu/h 7.33kW
- Multi-Comfort Air Control
- Weekly Timer
- Odour Wash
- Economy Mode

General Information	Indoor Model Number		CS-D24DB4H5
	Panel Model Number		CZ-BT03P
	Outdoor Model Number	Indoor [kW]	7.33
		Indoor [Btu/h]	25,000
	EER [W/W]		(220V)2.99
	(Cooling) [msup3/sup/min]		22.0
Healthy Air Quality Features		Super Allergu-Buster Filter	Optional
Comfortable Features	Low Ambient Cooling	Indoor (Cooling) High/Low [dB (A)]	(220V)38/35 (240V)39/36
		Outdoor (Cooling) High [dB (A)]	(220V)49 (240V)50
Product Dimensions	Indoor [mm]	Width	840.0
		Height	246.0
		Depth	840.0
	Panel [mm]	Width	950.0
		Height	950.0
		Depth	45.0
	Outdoor (per Unit) [mm]	Width	900.0
		Height	795.0
		Depth	320.0
Product Weight	Net Weight [kg]	Indoor	24.0
		Panel	4.5
		Outdoor	61.0
Electricity	Phase		1
	Rated Voltage		220V or 240V

	Power Frequency	Indoor (Cooling)	(220V)2.45Kw (240V)2.45Kw
Technical Features	Piping Connection	Liquid Side [mm]	9.52
		Liquid Side [inch]	3/8
		Gas Side [mm]	15.88
		Gas Side [inch]	5/8
	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)	40.0
		Maximum Pipe Height [m]	30.0
Maximum Changeless Length [m]		20.0	
Convenient Features		24-Hour ON OFF Real Setting Timer	Yes
		Wireless Remote Controller	Yes
Reliable Features	Long Piping (Numbers indicate the maximum pipe length)		40m
	Self-Diagnostic Function	Cooling	27C DB/19C WB 35C DB/24C WB

### CS-D28DB4H5 (3 HP)

## Non Inverter Cassette Type

- 29,000 Btu/h 8.50kW
- Multi-Comfort Air Control
- Weekly Timer
- Odour Wash
- Economy Mode

General	Indoor Model Number	CS-D28DB4H5
	Panel Model Number	CZ-BT03P
	Outdoor Model Number	(1 Phase)CU-D28DBH5 (3 Phase)CU-D28DBH8
	Indoor [kW]	8.50
	Indoor [Btu/h]	29,000
	EER [W/W]	(220V)3.27 [CU-D28DBH5] (240V)3.27 [CU-D28DBH5] (380V)3.27 [CU-D28DBH8] (415V)3.27 [CU-D28DBH8]
	(Cooling) [m3/min]	23.5
	Healthy Air Quality Features	Super Allergu-Buster Filter
Comfortable Features	Low Ambient Cooling	Yes
	Indoor (Cooling) High/Low [dB (A)]	(220V)41/37 [CU-D28DBH5] (240V)42/38 [CU-D28DBH5] (380V)41/37 [CU-D28DBH8] (415V)42/38 [CU-D28DBH8]

		Outdoor (Cooling) High [dB (A)]	(220V)51 [CU-D28DBH5] (240V)52 [CU-D28DBH5] (380V)51 [CU-D28DBH8] (415V)52 [CU-D28DBH8]
Product Dimensions	Indoor [mm]	Width	840
		Height	246.0
		Depth	840.0
	Panel [mm]	Width	950.0
		Height	950.0
		Depth	45.0
	Outdoor (per Unit) [mm]	Width	900.0
		Height	795.0
		Depth	320.0
Product Weight	Net Weight [kg]	Indoor	24.0
		Panel	4.5
		Outdoor	61.0
Electricity		Phase	1 or 3
		Rated Voltage	220-240V or 380-415V
		Power Frequency	50Hz
		Indoor (Cooling)	(220V)2.60kW [CU-D28DBH5] (240V)2.60kW [CU-D28DBH5] (380V)2.60kW [CU-D28DBH8] (415V)2.60kW [CU-D28DBH8]
Technical Features	Piping Connection	Liquid Side [mm]	9.52
		Liquid Side [inch]	3/8
		Gas Side [mm]	15.88
		Gas Side [inch]	5/8
	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)	40.0
		Maximum Pipe Height [m]	30.0
Maximum Changeless Length [m]		20.0	
Convenient Features		24-Hour ON & OFF Real Setting Timer	Yes
		Wireless Remote Controller	Yes
Reliable Features		Long Piping (Numbers indicate the maximum pipe length)	40m
		Self-Diagnostic Function	Yes
		Cooling	27C DB/19C WB 35C DB/24C WB

**CS-D34DB4H5 (4 HP)**

**Non Inverter Cassette Type**

- 39,000 Btu/h 11.44kW
- Multi-Comfort Air Control
- Weekly Timer
- Odour Wash
- Economy Mode

General Information	Indoor Model Number		CS-D34DB4H5	
	Panel Model Number		CZ-BT03P	
	Outdoor Model Number	Indoor [kW]	11.44	
		Indoor [Btu/h]	39,000	
	EER [W/W]		(380V)3.52	
	(Cooling) [msup3/sup/min]		24.0	
Healthy Air Quality Features		Super Allergu-Buster Filter	Optional	
Comfortable Features	Low Ambient Cooling	Indoor (Cooling) High/Low [dB (A)]	(380V)42/39 (415V)43/40	
		Outdoor (Cooling) High [dB (A)]	(380V)54 (415V)55	
Product Dimensions	Indoor [mm]	Width	840	
		Height	246.0	
		Depth	840.0	
	Panel [mm]	Width	950.0	
		Height	950.0	
		Depth	45.0	
	Outdoor (per Unit) [mm]	Width	900.0	
		Height	1170.0	
		Depth	320.0	
Product Weight	Net Weight [kg]	Indoor	25.0	
		Panel	4.5	
		Outdoor	83.0	
Electricity	Phase		3	
	Rated Voltage		380V or 415V	
	Power Frequency	Indoor (Cooling)	(380V)3.25kW (415V)3.25kW	
Technical Features	Piping Connection	Liquid Side [mm]	9.52	
		Liquid Side [inch]	3/8	
		Gas Side [mm]	19.05	
		Gas Side [inch]	3/4	
	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)		40.0
		Maximum Pipe Height [m]		30.0
Maximum Changeless Length [m]		20.0		
Convenient Features		24-Hour ON OFF Real Setting Timer	Yes	

	Wireless Remote Controller	Yes
Reliable Features	Long Piping (Numbers indicate the maximum pipe length)	40m
	Self-Diagnostic Function	Cooling 27C DB/19C WB 35C DB/24C WB

CS-D43DB4H5 (5 HP)

## Non Inverter Cassette Type

- 49,000 Btu/h 14.37kW
- Multi-Comfort Air Control
- Weekly Timer
- Odour Wash
- Economy Mode

General Information	Indoor Model Number		CS-D43DB4H5
	Panel Model Number		CZ-BT03P
	Outdoor Model Number	Indoor [kW]	14.37
		Indoor [Btu/h]	49,000
	EER [W/W]		(380V)3.53
(Cooling) [msup3/sup/min]		33.0	
Healthy Air Quality Features		Super Allergu-Buster Filter	Optional
Comfortable Features	Low Ambient Cooling	Indoor (Cooling) High/Low [dB (A)]	(380V)46/42 (415V)47/43
		Outdoor (Cooling) High [dB (A)]	(380V)55 (415V)56
Product Dimensions	Indoor [mm]	Width	840
		Height	288.0
		Depth	840.0
	Panel [mm]	Width	950.0
		Height	950.0
		Depth	45.0
	Outdoor (per Unit) [mm]	Width	900.0
		Height	1170.0
		Depth	320.0
Product Weight	Net Weight [kg]	Indoor	30.0
		Panel	4.5
		Outdoor	83.0
Electricity	Phase		3
	Rated Voltage		380V or 415V
	Power Frequency	Indoor (Cooling)	(380V)4.07kW (415V)4.07kW
Technical Features	Piping Connection	Liquid Side [mm]	9.52
		Liquid Side [inch]	3/8
		Gas Side [mm]	19.05

		Gas Side [inch]	3/4
	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)	40.0
		Maximum Pipe Height [m]	30.0
		Maximum Changeless Length [m]	20.0
Convenient Features		24-Hour ON OFF Real Setting Timer	Yes
		Wireless Remote Controller	Yes
Reliable Features	Long Piping (Numbers indicate the maximum pipe length)		40m
	Self-Diagnostic Function	Cooling	27C DB/19C WB 35C DB/24C WB

### CS-D50DB4H5 (6 HP)

## Non Inverter Cassette Type

- 54,600 Btu/h 16.00kW
- Multi-Comfort Air Control
- Weekly Timer
- Odour Wash
- Economy Mode

General Information	Indoor Model Number		CS-D50DB4H5
	Panel Model Number		CZ-BT03P
	Outdoor Model Number	Indoor [kW]	16.00
		Indoor [Btu/h]	54,600
	EER [W/W]		(380V)3.30
(Cooling) [msup3/sup/min]		33.0	
Healthy Air Quality Features		Super Alleru-Buster Filter	Optional
Comfortable Features	Low Ambient Cooling	Indoor (Cooling) High/Low [dB (A)]	(380V)47/43 (415V)48/44
		Outdoor (Cooling) High [dB (A)]	(380V)55 (415V)56
Product Dimensions	Indoor [mm]	Width	840
		Height	288.0
		Depth	840.0
	Panel [mm]	Width	950.0
		Height	950.0
		Depth	45.0
	Outdoor (per Unit) [mm]	Width	900.0
		Height	1170.0
		Depth	320.0
Product Weight	Net Weight [kg]	Indoor	30.0
		Panel	4.5

		Outdoor	83.0	
Electricity	Phase		3	
	Rated Voltage		380V or 415V	
	Power Frequency	Indoor (Cooling)	(380V)4.85kW (415V)4.85kW	
Technical Features	Piping Connection	Liquid Side [mm]	9.52	
		Liquid Side [inch]	3/8	
		Gas Side [mm]	19.05	
		Gas Side [inch]	3/4	
	Pipe Length	Maximum Pipe Length [m] (Additional gas may be required for some models)		40.0
		Maximum Pipe Height [m]		30.0
Maximum Changeless Length [m]		20.0		
Convenient Features		24-Hour ON OFF Real Setting Timer	Yes	
		Wireless Remote Controller	Yes	
Reliable Features	Long Piping (Numbers indicate the maximum pipe length)		40m	
	Self-Diagnostic Function	Cooling	27C DB/19C WB 35C DB/24C WB	

**Daikin - Panasonic - Toshiba - Mitsubishi - Sanyo  
Sharp - Carrier - Trane - Reetech - LG - Samsung  
Hitachi - Sumikura - Nagakawa - Midea - Gree...**



**TƯ VẤN - THIẾT KẾ  
THI CÔNG - SỬA CHỮA  
Hợp đồng bảo trì dài hạn**

**CUNG CẤP THIẾT BỊ CHÍNH HÃNG**

**Call: 0903152320 - Email: auvietetc@gmail.com**

**Panasonic - Shneider - Ls - Mitsubishi  
Fuji - Shihlin - Delixi - Fuji - Chint...**

**CB - MCB - MCCB - ELCB - RCCB/RCBO - ACB  
Contactor - Relay nhiệt - Phích & ổ cắm công nghiệp  
Đèn báo - Nút nhấn - Contact - Đồng hồ A, V...**